

GAS MIXERS

www.wittgas.com

KM 100/200-2MEM



KM 100/200-3MEM



Mixer for 2 or 3 defined gases especially for vacuum packing machines in the food industry and for applications where the mixed gas flow fluctuates widely.

Easy Usage

- a proportional mixing valve with percentage scale provides an infinitely variable mixture setting
- these mixers require a receiver with sufficient volume (min. 10 litres volume), which ensures a constant, accurate mixture when large or very small volumes are needed

Constant Quality

- independent of pressure fluctuations
- independent of packing speed
- independent of size of packaging

High Process Safety

- the gas supply is monitored by pressure switches. A low pressure triggers an optical alarm (audible alarm optional) and a potential-free contact (e.g. to shut down machinery and avoid quality problems)
- lockable inspection transparent door for protection of settings

Maximum Hygiene

- splash-proof, robust stainless steel housing
- smooth and easy to clean surface for perfect hygiene

Please identify the individual gases at the time of enquiring!

Type	KM 100/200 -2MEM /3MEM
Gases	N ₂ , CO ₂ , O ₂ not for flammable gases!
Mixing Range	0 – 100%
Gas inlet pressure	max. 290 psi
Inlet pressure differential between the gases	max. 43.5 psi
Gas outlet pressure	see table
Mixture output (air)	see table
Setting accuracy	±2% (scale 0-100%) abs.
Mixture accuracy	better±1% abs.
Gas connections	G 3/8 with cone seat, 8 mm hose nipple

Casing	stainless steel, splashproof
Weight	approx. 39.7 lb (2MEM), 57.3 lb (3MEM)
Dimensions (HxWxD)	approx. 8.8 x 12.8 x 13.6 inch (without connections)
Voltage	230 V AC, 110 V AC, 24 V DC
Power consumption	230 V AC / 0.07 A 110 V AC / 0.11 A 24 V DC / 0.4 A
Approvals	Company certified according to ISO 9001:2000, ISO 14001 and ISO 22000 CE-marked for: - EMC 2004/108/EC - Low Voltage Directive 2006/95/EC

Flow (in SCFH) in relation to air		min. receiver pressure in psig (max. receiver pressure 7.2 psi higher)											
		21.7	36.3	50.8	65.3	79.8	94.3	108.8	123.3	137.8	152.3		
min. inlet pressure in psig (max. 290 psi)	58.0	343.3	–	–	–	–	–	–	–	–	–	–	–
	72.5	442.8	404.7	–	–	–	–	–	–	–	–	–	–
	87.0	531.8	523.4	460.0	–	–	–	–	–	–	–	–	–
	101.5	620.8	620.8	593.3	508.5	–	–	–	–	–	–	–	–
	116.0	709.8	709.8	703.5	656.8	553.0	–	–	–	–	–	–	–
	130.5	796.7	796.7	796.7	777.6	714.1	593.3	–	–	–	–	–	–
	145.0	885.7	885.7	885.7	881.5	845.4	767.0	631.4	–	–	–	–	–
	159.5	974.7	974.7	974.7	974.7	957.7	906.9	815.8	667.4	–	–	–	–
	174.0	1063.7	1063.7	1063.7	1063.7	1059.4	1029.8	966.2	862.4	703.5	–	–	–
	188.5	1152.7	1152.7	1152.7	1152.7	1152.7	1137.8	1095.5	1021.3	906.9	735.2	–	–

Product Information

Technical Data

A01/G0 subject to change