

WITT-SWITCH

Control Unit for pressure regulating stations



Switch and Control Unit for automatic change over of pressure regulating stations. Provides a smooth process flow and optimal results with a continuous gas flow.

Benefits

- intelligent control, - the last selected gas supply will be activated after an emergency stop
- freely selectable side for starting
- compatible with WITT-Pressure regulating station
- quick and easy wall mounting
- optimal draw down of cylinder
- audible and visual alarm
- status indication by illuminated push-button and display
- integrated emergency cut-out

Operation / Usage

- for automatic change over of pressure regulating stations for continuous gas withdrawal
- applicable for switching an emergency supply

Function

- automatic change over with controlled limit values by two solenoid valves between two connected cylinders or cylinder bundles

Options

- additional audible alarm device
- flashing beacon

Approvals

Company certified according to ISO 9001

Technical Data	
Order-No.	194-019
Voltage	230 V AC, 24 V DC
Power consumption	0.4 A
Housing	polycarbonate (plastic material)
Enclosure rating	IP65
Temperature range	0 °C up to 55 °C 32 °F up to 131 °F
Dimensions	
Height	approx. 310 mm (12.20 inches)
Width	approx. 330 mm (12.99 inches)
Depth	approx. 175 mm (6.89 inches)
Weight	approx. 3.0 kg