



MG 50-2ME GB

MG 50-3ME Ex

Gas mixing systems for 2 or 3 defined gases, designed for a variety of industrial applications with high flows and fluctuating gas mixture production requirements.

Capacity range from 0 to approx. 161 Nm³/h.
For the exact pressure and flow capacity ratios, please see the technical data overleaf.

Note:

System only works with sufficient buffer volume (100 to 250 litres depending on gas mixing capacity).

Easy operation

- a proportional mixing valve (-2ME) or three single mixing valves (-3ME), each with a control knob and %-scale, provide infinitely variable mixture settings
- gas mixture withdrawal possible from zero to the maximum flow capacity

High process reliability

- independent of pressure fluctuations in the gas supply
- intermittent gas mixture withdrawal possible
- lockable transparent door for protection of settings
- splash-proof and robust stainless steel housing

Options

- for flammable gases available as Ex-version with separate control cabinet
- without electrical equipment as MP-version
- alarm module AM3: integrated inlet pressure monitoring with digital display for pressure (with analog pressure transmitters) plus optical alarm, adjustable alarm limits, obligation of acknowledgement, protection of alarms, interfaces for controlling external alarms etc.
- integrated gas analysis for the monitoring/control and documentation of the gas mixture production
- gas mixer mounted on gas mixture buffer tank for a more convenient installation

Other models, options and accessories available upon request.

Please identify the individual gases at the time of enquiring!

GAS MIXER MG 50/100-ME



Type	MG 50/100-2ME /-3ME; MG 50/100-2ME /-3ME Ex
Gases	all technical gases (excluding toxic or corrosive gases)
Mixing range	0-25% or 0-100% by selection of suitable mixing range the accuracy corresponds to ISO 14175
Pressure settings	see tables
Inlet pressure differential between the gases	max. 3 bar
Mixture output (air)	see tables
Setting accuracy	±1% abs. (scale 0-25%), ±2% abs. (scale 0-100%)
Mixing precision	better than ±1% abs.
Gas connections MG 50	
inlets	G 1/2 RH with cone, soldering nipple for pipe OD 15 mm
outlet at mixer	G 1/2 RH with cone, soldering nipple for pipe OD 15 mm
outlet at receiver	WITTFIX-Pipe Couplers for pipe OD 22x1.5 mm
Gas connections MG 100	
inlets	G 1 RH with cone, soldering nipple for pipe OD 22 mm
outlet at mixer	G 1 RH with cone, soldering nipple for pipe OD 22 mm
outlet at receiver	WITTFIX-Pipe Couplers for pipe OD 22x1.5 mm
Housing	stainless steel, splash proof (not Ex-version)
Weight MG 50	approx. 35 kg (-2ME), approx. 50 kg (-3ME) without receiver
Weight MG 100	approx. 38 kg (-2ME), approx. 53 kg (-3ME) without receiver
Dimensions (HxWxD)	
mixer	approx. 330 x 485 x 500 mm (12.99 x 19.09 x 19.68 inches) (without connections and receiver)
separate control cabinet (Ex)	approx. 280 x 302 x 158 mm (11.02 x 11.89 x 6.22 inches) (without connections)
Voltage	230 V AC, 110 V AC or 24 V DC
Power consumption	230 V AC, 0.07 A
Approvals	Company certified according to ISO 9001 and ISO 22000 CE-marked according to: - EMC 2014/30/EU - Low Voltage Directive 2014/35/EU - PED 2014/68/EU - ATEX 114 Directive 2014/34/EU for food-grade gases according to: - Regulation (EC) No 1935/2004 Designed for Oxygen Service in accordance with EIGA 13/20, CGA G-4.4 and AIGA 021/20: Oxygen Pipeline and Piping Systems Cleaned for Oxygen Service in accordance with EIGA 33/18, CGA G-4.1 and AIGA 012/19: Cleaning of Equipment for Oxygen Service

		min. receiver pressure in barg (max. receiver pressure 0.5 bar higher)									
		1.5	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5	10.5
min. inlet pressure in barg (max. 20 bar)	4	21	-	-	-	-	-	-	-	-	-
	5	27	24	-	-	-	-	-	-	-	-
	6	32	32	28	-	-	-	-	-	-	-
	7	37	37	36	31	-	-	-	-	-	-
	8	43	43	43	40	33	-	-	-	-	-
	9	48	48	48	47	43	36	-	-	-	-
	10	54	54	54	53	51	46	38	-	-	-
	11	59	59	59	59	58	55	49	40	-	-
	12	65	65	65	65	64	62	59	52	42	-
	13	70	70	70	70	70	69	67	62	55	44

		min. receiver pressure in barg (max. receiver pressure 0.5 bar higher)									
		1.5	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5	
min. inlet pressure in barg (max. 20 bar)	4	37	-	-	-	-	-	-	-	-	
	5	53	45	-	-	-	-	-	-	-	
	6	67	62	49	-	-	-	-	-	-	
	7	80	77	69	53	-	-	-	-	-	
	8	93	91	86	75	60	-	-	-	-	
	9	106	105	100	93	82	63	-	-	-	
	10	119	118	115	109	101	87	68	-	-	
	11	133	132	130	126	119	108	93	72	-	
	12	147	146	144	142	137	128	116	98	75	
	13	161	160	158	156	152	147	137	123	104	